



PPO Smart Imaging System Specifications

(Z-Configuration Inspection)

PPO's Smart Imaging System is a proven solution for both detecting and classifying foreign materials and assessing quality, detecting issues such as woody breast, fat/lean composition, tenderness, and more. The system is designed for non-invasive, double-sided inspection and meets all applicable food-safe sanitary design principles and standards including NAMI and CFIA, and is IP69K compliant.

Compressed Air		Environmental		
Pressure 80 PSI minimum 145 PSI maximum Consumption 35 CFM maximum (actual consumption dependent on product quality) Supply Quality 7:4:4 as per ISO 8573.1 5 micron filtration		Standard Operating Temperature Range 0C to +10C Non-operating Temperature Range -25C to +60C (Transportation and storage) Humidity 90% R.H. maximum, non-condensing Ingress protection rating IP69K or equivalent Clean Air Intake Measurements: Intake Air Consumption: 400 CFM MIN Intake Air: 2-8°C		
Speed Capability	Size/Weight	HMI/PLC	Electrical	Connectivity
Supports line speeds up to 120 ft/minute and up to 50,000 lbs/hr, depending on the application	Conveyor Belt width (in-feed and out-feed): 30 inches (physical width) Customizable per application	10 Inch Touch Screen Panel (IP67, encased touch screen) PLC: Allen Bradley Compact Logix	Power Consumption 3 Phase, 480V, 35A	Single Gigabit Ethernet port (RJ-45), with appropriate controls to allow access via VPN



